

G1-38X



**High precision&stability
of magnetic compensator**



- High precision & stability of magnetic compensator
- Key components for imported materials
- Uniquely 38X
- Objective aperture 46mm.
- Accuracy without micrometer $\leq 0.7\text{mm}$.
- IPX6 water proection

Specification :

Technical	G1-38X
1 Km Error	38X
Magnification	46 mm.
Objective aperture	$\leq 0.7\text{mm}$.
Resolution	$\leq 3.0''$
Angle of View	$1^{\circ} 20'$
Image	Erect
Reticle	Wedge
Min View Distance	$\leq 0.3\text{m}$.
View Distance Error	$\leq \pm 0.4\%$
Focusing Error	$\leq 0.5\text{m}$.
Compensator	Magneticdamper
Working Range	$\leq 15'$
Compensating Error	$\leq 0.2'$
Setting Accuracy	$\leq 0.3'$
Setting Time	$\leq 2\text{s}$
Bubble	8'/2mm.
Scale	1'or 1 Gon
Water Impervious	IPX6
Accessories	Manual,Plumb bob,Allen Key,Adjusting pin, Downy cloth,Sicdative each one
Weight	N,W:2.0Kg. G.w:3.0kg.
Package	1 piece in 1 plastic carton, 4 pieces in 1 carton

Magnification
38X

Water Impervious
IP X6

Caliber
Ø46mm

1 km Error
 $\leq 0.5 \text{ mm}$

Working Range
 $\geq \pm 15'$

Min view Distance
1 M

Resolution
 $\leq 3''$

