# Set up to cost effective and accurate leveling work

**AP-220 LEVEL IS A PERFECT ENTRY** LEVEL DESIGNED FOR EASE OF USE AND **GUARANTEED PRODUCTIVITY** 

#### **Features and Benefits**

- Very Short Focusing Distance: 0,3m
- Optimal for close range work
- Robust construction: Metal top cover
- Weather and Dust Resistance: IP55
- An easy-to-read horizontal circle
- Magnetic damped automatic compensator for rapid and accurate results
- Light Weight: 1,25 kg

AP-224 (24 x) AP-228 (28 x) AP-230 (30 x)

### **Standard configuration**

- Carrying case
- Plumb bob
- User-manual

PENTAX a world-renowned brand with a world-wide service network.







# **PENTAX**

## **Technical specifications**

AP-220 Series	AP-230	AP-228	AP-224
Telescope			
Image		Erect	
Magnification	30x	28x	24x
Objective Aperture		ф30 mm	
Resolving Power	3"	3"	3.5"
Field of view		1°20′	
Minimum Focus Distance		0.3 m	
Stadia ratio		100	
Stadia constant		0	
Accuracy			
Standard Deviation of 1km			
double run leveling	1.5 mm	1.5 mm	2 mm
Automatic Compensator			
Working range		±15′	
Туре		Magnetic	
Circular Vial			
Sensitivity		8' / 2mm	
Horizontal Circle			
Minimum division		1° / 1gon	
Reading system		Total area 400G/360°	
Size and Weight			
Dimensions	130mm x 140mm x L 200mm		
Weight		1.25 kg	
Dust and Water resistance		IP55	

<sup>\*</sup> Specifications are subject to change without notice

#### TI Asahi Co., Ltd.

#### **International Sales Department**

4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi Saitama, 339-0073 Japan Tel.: +81-48-793-0118 Fax. +81-48-793-0128 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/



Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.

**JSIMA** 

Your Official Pentax Dealer



# **Basic Applications**

**Parallels** 

AP-224 | AP-228 | AP-230

## Simple, accurate, optimal for use in:

- General Building and Construction
- Civil Engineering
- Landscaping







