

**Leica DISTO™
D110 & D2**



IP 54

ISO
16331-1



 **Swiss Technology**
by Leica Geosystems



NEW

The original laser distance meter

Leica DISTO™ D110 & D2



Leica DISTO™ D110

Small size – great possibilities



Always at hand

The removable pocket clip is a clever accessory for carrying the Leica DISTO™ D110 on your clothing. Use it to attach the unit to your trousers, shirt or jacket so that you have it always at hand.



Small and handy

The Leica DISTO™ D110 is the smallest and lightest laser distance meter in the DISTO™ product range. With an ergonomic shape, it fits perfectly into your hand and is effortless to use. The self-explanatory keys ensure operation is quick and intuitive.

Bluetooth® Smart and Leica DISTO™ Sketch app



Extended functionality by pressing a button

The smart App "Leica DISTO™ sketch" is the ideal link between the Leica DISTO™ with Bluetooth® Smart and a smartphone or a tablet. It allows you to create and precisely dimension sketches and pictures. The files can then be sent directly to the office. This simplifies and speeds up work flow.

Leica DISTO™ D2

Many functions – long range

Multifunctional end piece

Whether you are taking measurements from corners, grooves or edges, with the multifunctional end piece you can always accurately position the Leica DISTO™ D2. The position of the end piece is automatically detected and taken into account. This prevents expensive measuring errors.



Versatile thanks to useful measuring functions

Functions such as addition and subtraction, area and volume calculations make every measurement task child's play. The instrument stores the last 10 measurement results.



Free app:
Leica DISTO™ sketch



Available on the
App Store



GET IT ON
Google play



Technical data	DISTO™ D110	DISTO™ D2
Typ. measuring accuracy	± 1.5 mm	± 1.5 mm
Range	0.2 up to 60 m	0.05 up to 100 m
Measuring units	m, ft, in	m, ft, in
X-Range Power Technology	●	●
Display illumination	●	●
Free App	●	●
Data interface*	Bluetooth® Smart	
Battery life time**	up to 10,000 measurements up to 20 h of operation	
Batteries	type AAA, 2 × 1.5 V	
Protection class	IP 54 (dust and splash water protected)	
Dimensions	120 × 37 × 23 mm	116 × 44 × 26 mm
Weight with batteries	92 g	100 g

*) System requirements and other details can be found at www.disto.com

**) Reduced in Bluetooth® Smart mode

Functions	DISTO™ D110	DISTO™ D2
Distance measurement	●	●
Addition / subtraction	○	●
Area measurements	●	●
Volume measurement	○	●
Memory	○	10 results
Automatic end piece	○	●

PROTECT is subject to Leica Geosystems International Limited Warranty and PROTECT General Terms & Conditions set out under www.leica-geosystems.com/protect.

* Available through free online registration within 8 weeks from the purchase date.



Laser class 2
in accordance with IEC 60825-1

Dealer stamp

- when it has to be **right**

Leica
Geosystems