

PENTAX

Positioning Systems

G5 Series

G5Tw | G5Tt | G5Nw | G5Nt

Precision Satellite Surveying
with Wireless Communications

GPS | GLONASS | BEIDOU | SBAS
GALILEO (G5Tw & G5Tt ONLY)



- + New 3.5G GSM module for better performance
- + Rugged shape and robust styling with rubber
- + Better dust and weather resistance (IP67)
- + Equipped with TILT sensor that works as an electric bubble (G5Tt & G5Nt only)
- + WiFi for direct communication with web browser for e.g. downloading data, firmware upgrades and communication between receiver and controller

TI Asahi Co.,Ltd
Aiming at the future together!

GNSS SPECIFICATIONS

Model		G5Tw	G5Tt	G5Nw	G5Nt
Channel Configuration		220-channels (dual frequency) for GPS, GLONASS, Galileo, Beidou and SBAS		120-channels (dual frequency) for GPS, GLONASS, Beidou and SBAS	
Receiver Board		Trimble BD970		NovAtel 628	
Single Tracked	GPS	L1 C/A, L2E, L2C, L5		L1, L2, L2C	
	GLONASS	L1C/A, L1P, L2C/A (M only), L2P		L1, L2	
	BEIDOU			B1 / B2	
	Galileo	L1BOC, E5A, E5B, E5AltBOC		—	
	QZSS	L1 C/A, L1 SAIF, L2C, L5		—	
	SBAS	L1 C/A, L5		—	
Position Accuracy		Horizontal / Vertical			
	SBAS	0.5 m / 0.85 m		0.6 m	
	DGPS	0.25 m +1 ppm / 0.5 m + 1ppm		0.4 m	
RTK Performance	Horizontal Accuracy	0.008 m + 1 ppm		0.010 m + 1 ppm	
	Vertical Accuracy	0.015 m + 1 ppm		0.020 m + 1 ppm	
	Average Time to Work	Typ. < 10 sec.			
	Availability / Initialization Reliability	> 99.9%			
Static Performance	Horizontal Accuracy	2.5 mm + 0.5 ppm			
	Vertical Accuracy	5 mm + 0.5 ppm			
Ports		Lemo 5-pin, external radio and power supply			
		Lemo 7-pin, serial port and USB			
Internal Radio Modem	Frequency	410 ~ 470 MHz			
	Output Power	1 W			
GSM/GPRS Modem		Telit HE910-D			
		UMTS / HSPA+ / GSM / GPRS / EDGE (supporting NTRIP)			
Power	Internal Battery	3,350 mAh / 7.4V x2			
	Current Drain	0.45A / 12V			
		1.5A / 12V max.			
	Battery Running Time	Approx. 10 hr: Rover, 8 hr: Base			
Weight		1.5 kg with 2 batteries			
Dimensions		Ø 186 mm x H 89.7 mm			
Environmental Specifications	Operating Temperature	-20 °C to +65 °C			
	Storage Temperature	-20 °C to +65 °C			
	Shock/Drop	2 m			
Velocity Accuracy	Standalone	0.007 m/sec, 0.020 m/sec		0.03 m/s RMS	
Data Output		up to 50 Hz		up to 5 Hz	
		1 Hz, 2Hz, 5 Hz, 10 Hz, 20 Hz, 50 Hz		1 Hz, 5 Hz	
		RTCM Ver 2.1, 2.2, 2.3, 3.0, 3.1, 3.2			
		CMR, CMR+, sCMRx			
Time to First Fix	Cold Start	< 45 sec		< 50 sec	
	Warm Start	After power-on < 30 sec		After power-on < 35 sec	
		Re-acquisition < 2 sec		Re-acquisition < 1 sec	
WiFi		IEEE 802.11b/g			
Tilt Sensor		—	Electric Bubble	—	Electric Bubble
Bluetooth		Class 2			
Memory		MicroSD 4 GB			
RoHS		—			
Waterproofing		IP67			
Certification		CE			
Standard Accessories		2 x Li-Ion rechargeable battery pack			
		Battery charger + AC Adapter			
		4 GB MicroSD Card			
		UHF radio antenna (longer one)			
		5/8 inch screw adapter			
		Lemo 7-pin communication cable			

PENTAX Positioning System is dedicated to providing customers with first class positioning system products and freedom of choice. We have carefully designed high-quality products to meet the needs of today's surveyors based on the experience of many years involved in instrument design and construction. Our engineers have been involved in Survey products since the beginning of the Satellite Surveying Era. We are committed to ease of use, a low cost of ownership and flexibility to accommodate different working environments. Our close partners are carefully chosen and are committed to these values as we are.

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.



Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.